



**HIGH-CAPACITY FILING  
CABINET CERTIFIED FOR  
UP TO TWO HOURS'  
FIRE PROTECTION**



# FIRE FILE 31"

FIRE RESISTANT DOCUMENT PROTECTION




UL 72  
Class 350 2h

## KEY FEATURES

- Certified according with UL standard 72 in Class 350 Endurance for 2 hour duration.
- Maximised capacity to take full advantage for all storage needs.
- Each drawer is fire-protected. Even if one of the drawers is accidentally left open, the other closed drawers are still protected by the built in fire resistance partitions.
- Fitted with high-security locks as standard.
- Easy-to-operate day catch to secure the drawers when closed. Units do not have to be locked to provide fire protection but just to be pushed closed.
- High-quality steel sliders to ensure comfortable operation and full drawer access.
- Lighter weight construction which means smoother transportation and installation.
- Interlocking system that prevents more than one drawer being open at once and eliminates risk of tipping.
- Light grey, powder-coated finish and modern design which blends nicely into any office environment.
- Manufactured in accordance with ISO 9001 for quality management systems and ISO 14001 for environmental management systems.

# FIRE FILE 31"

## PRODUCT SPECIFICATIONS



Model	External height (mm)	External width (mm)	External depth (mm)	Drawer height (mm)	Drawer width (mm)	Drawer depth (mm)	Capacity (litres)	Weight (kg)
4 drawers – 2h	1510	551	779	290	387	604	272	328

### LOCKS



Chubb safes' Fire File 31" models are fitted with high-security locks as standard. They can be equipped with a central key lock for single locking or together with a mechanical combination lock for dual central locking. Each individual drawer can also be fitted with a keylock.



### FINISH

Colour: Light Grey RAL 7035

### FIRE TESTING

Chubb safes' Fire File 31" cabinets are tested and certified in accordance with the most common and well-established UL (Underwriter's Laboratories) Standard 72 to Class 350 for both 1-hour and 2-hour fire endurance.

The products are subjected to extensive fire testing which simulates the impact of a severe fire. This two-step process includes the following:

#### STEP 1

The filing cabinet is placed in a furnace and heated to a temperature of 1000°C or over, depending on the certification level. The furnace is switched off after one hour or two hours, depending on the certification level. The unit remains in the furnace until the temperature returns to ambient levels. The content is then examined for signs of damage. Both during furnace heating and the subsequent cooling period, the recorded internal temperature must not have exceeded 177°C (or 350°F).

#### STEP 2

Fire explosion or Shock test. To simulate sudden heating, possibly as a result of rapid fire spread, the cabinet is inserted into a preheated furnace. The stresses and strains created by such rapid heating can easily cause a poorly constructed unit to fail. At no point are internal temperatures allowed to exceed those specified for the fire endurance test in Step 1.

Authorised dealer

[www.chubbsafes.com](http://www.chubbsafes.com)